

INDEPENDENT

Electric Vehicle Battery Certificate

Certificate issued by



Certificate creation time: 2026-09-17, 11:12

Certificate number: 20260917.112

Vehicle information

Registration number / VIN	Brand / Model	Odometer	Battery type	Charging port type
JEJ02R / WBY41DU02PSA34263	BMW iX3	47160 km	NMC	CCS


Test results

Date and time of test: 2026-09-17, 10:58

Test performed by:

kvd bil

State of health (SOH)



97 %

Battery capacity

Estimated capacity	71.9 kWh
Factory new capacity	74.0 kWh

WLTP range

Estimated WLTP	445 km
Factory new WLTP	458 km

Diagnostics

	MIN	MAX	DELTA
Battery temperature	15.4°C	16.4°C	1.1°C
Cell voltage	3.966V	4.023V	57mV

Cell voltages

1-24	4.010	4.000	3.993	4.006	3.993	4.009	4.005	4.020	4.014	3.998	4.012	4.001	3.990	3.995	4.004	3.990	3.990	4.003	4.003	3.989	3.989	3.992	3.996	4.007
25-48	4.013	3.995	3.993	3.991	4.001	3.992	4.017	3.996	3.990	3.987	3.992	3.990	4.004	3.984	3.990	3.996	3.998	3.998	3.994	3.993	4.001	3.996	3.991	3.996
49-72	4.001	4.010	4.008	4.004	3.990	3.982	3.992	3.991	3.995	4.023	4.002	4.004	3.990	3.977	3.966	3.978	4.001	3.982	3.982	3.995	3.985	3.996	3.985	3.992
73-94	3.990	3.990	3.995	3.994	4.001	3.995	3.992	3.995	3.997	4.002	3.994	3.998	3.998	4.006	4.015	3.997	4.010	4.009	4.010	4.000	3.996	3.994		

Normal: Cell voltage deviation is within the expected range.

Method and control

Battery assessment is based on diagnostic data retrieved from the vehicle's OEM Battery Management System (BMS) and comparative reference data from similar vehicle models.

Attest

The test was executed according to the Optiledger SOH procedure with no known technical issues during data acquisition.

Disclaimer

Results represent an estimated assessment of battery condition at the time of testing and do not constitute a warranty or guarantee of battery capacity, performance, or remaining lifetime. The original WLTP range is determined and published by the vehicle manufacturer under standardized laboratory test conditions. The estimated WLTP presented in this report is calculated from diagnostic data and reference parameters and does not represent actual driving range. Real-world range may vary depending on driving conditions, temperature, load, and driving behavior. Full methodology, limitations and liability disclaimer available at: https://optiledger.se/legal/optiledger_battery_test_methodology_and_disclaimer.pdf.